



AUHW Series

Warning Light & Electronic Horn Combination



Nomenclature



AUHW -	①	-	②	-	③	-	④
	Type		Audible Option		Voltage		Color
Warning Light & Electronic Horn Combination	L 100		AM : Melody AB : Buzzer		110 : AC110V 220 : AC220V 12 : DC12V 24 : DC24V		R : Red Y : Yellow G : Green



AUHW

Warning Light & Electronic Horn Combination

- Transmits visual and auditory signals simultaneously
- Structure combining LED indicator light and high-quality electronic horn
- Clear sound quality with 8-code high-quality output
- 16 modes of tone combination possible by internal DIP S/W operation
- Built-in LED lighting-flashing switch S/W, volume size adjustable depending on application environment
- Max Volume : Max. 105dB
- IP Rating : IP54
- Materials : Globe[PC], Body[ABS], Reflector [Heat resistant type ABS]
- Operating Temperature : -20 ~ 40°C

Customization

- ※ Users can control sound combinations through the DIP switches in the product. (See Page 68)
- ※ Settings other than the basic factory specifications (AM, AB) are possible through DIP S/W settings inside the product.
- ※ You can order by setting the desired settings according to the order specifications.

MODEL	S/W Basic Setting	Channel	Audible Option	Voltage	Current	Color
AUHW-L100-AM	ON OFF Dip switches 2,3,4 ON	A1 (Yellow) A2 (Green) A3 (Blue) A4 (White)	Turkish March Piano Sonatas Home Sweet Home Fur Elise	AC110V AC220V DC12V DC24V	0.056A 0.028A 0.15A 0.20A	● Red ● Yellow ● Green
AUHW-L100-AB	ON OFF Dip switches 1,2 ON	A1 (Yellow) A2 (Green) A3 (Blue) A4 (White)	beep ~ beep ~ beep Ding Dong beep-ee beep beep beep beep			

Technical Diagram & Wiring Instructions

Unit: mm

